




Compression Fittings - Series SF and DF




A range of stainless steel and brass compression fittings designed for use with temperature sensors.

Single or Double ferrule versions are available in a wide range of thread sizes to suit diameters from 0.5mm to 21.3mm.


Compression Fittings

We offer both single and double ferrule compression fittings.

SF Series - Single Ferrule Compression Fittings




DF Series - Double Ferrule Compression Fittings



Compression Fittings

SFS Single Ferrule 316 Stainless Steel Fittings - BSPT Threads




Spare / replacement olives are available.
Please see page 8 for details.

| Thread Size | To suit probes with the following diameters | | | | | | | | | |
|-------------|---|-----------|-----------|-----------|------------------|-----------|-----------|-----------------|----------|-------------------|
| | 0.5mm | 0.75mm | 1.0mm | 1.5mm | (1/16") 1.6mm | 2.0mm | 3.0mm | (1/8") 3.2mm | 4.5mm | (3/16") 4.76mm |
| 1/16" BSPT | SFS116T05 | — | SFS116T10 | SFS116T15 | SFS116T16 | SFS116T20 | SFS116T30 | — | — | — |
| 1/8" BSPT | SFS18T05 | SFS18T075 | SFS18T10 | SFS18T15 | SFS18T16 | SFS18T20 | SFS18T30 | SFS18T32 | SFS18T45 | SFS18T47 |
| 1/4" BSPT | — | — | SFS14T10 | SFS14T15 | SFS14T16 | SFS14T20 | SFS14T30 | SFS14T32 | SFS14T45 | SFS14T47 |
| 3/8" BSPT | — | — | — | — | — | — | SFS38T30 | SFS38T32 | SFS38T45 | SFS38T47 |
| 1/2" BSPT | — | — | SFS12T10 | SFS12T15 | — | — | SFS12T30 | SFS12T32 | SFS12T45 | SFS12T47 |
| 3/4" BSPT | — | — | — | — | — | — | SFS34T30 | — | — | — |

| Thread Size | To suit probes with the following diameters | | | | | | | | | |
|-------------|---|----------|-----------------|------------------|----------|-----------------|-----------|------------------|------------------|--------------------|
| | 7/32" 5.5mm | 6.0mm | (1/4") 6.4mm | (5/16") 7.9mm | 8.0mm | (3/8") 9.5mm | 12.0mm | (1/2") 12.7mm | (5/8") 15.9mm | (13/16") 21.3mm |
| 1/8" BSPT | SFS18T55 | SFS18T60 | SFS18T64 | — | — | — | — | — | — | — |
| 1/4" BSPT | SFS14T55 | SFS14T60 | SFS14T64 | SFS14T79 | SFS14T80 | — | — | — | — | — |
| 3/8" BSPT | SFS38T55 | SFS38T60 | SFS38T64 | SFS38T79 | SFS38T80 | SFS38T95 | — | SFS38T127 | — | — |
| 1/2" BSPT | SFS12T55 | SFS12T60 | SFS12T64 | SFS12T79 | SFS12T80 | SFS12T95 | SFS12T120 | SFS12T127 | SFS12T159 | — |
| 3/4" BSPT | — | SFS34T60 | SFS34T64 | SFS34T79 | SFS34T80 | SFS34T95 | SFS34T120 | SFS34T127 | SFS34T159 | SFS34T213 |
| 1" BSPT | — | SFS1T60 | SFS1T64 | SFS1T79 | SFS1T80 | — | SFS1T120 | SFS1T127 | SFS1T159 | SFS1T213 |

Other thread sizes are available, please contact us for details.

SFS Single Ferrule 316 Stainless Steel Fittings - BSPP Threads



Spare / replacement olives are available.
Please see page 8 for details.


| Thread Size | To suit probes with the following diameters | | | | | | | | | |
|-------------|---|-----------|-----------|-----------|------------------|-----------|-----------|-----------------|----------|-------------------|
| | 0.5mm | 0.75mm | 1.0mm | 1.5mm | (1/16") 1.6mm | 2.0mm | 3.0mm | (1/8") 3.2mm | 4.5mm | (3/16") 4.76mm |
| 1/16" BSPP | SFS116P05 | — | SFS116P10 | SFS116P15 | SFS116P16 | SFS116P20 | SFS116P30 | — | — | — |
| 1/8" BSPP | SFS18P05 | SFS18P075 | SFS18P10 | SFS18P15 | SFS18P16 | SFS18P20 | SFS18P30 | SFS18P32 | SFS18P45 | SFS18P47 |
| 1/4" BSPP | — | — | SFS14P10 | SFS14P15 | SFS14P16 | SFS14P20 | SFS14P30 | SFS14P32 | SFS14P45 | SFS14P47 |
| 3/8" BSPP | — | — | — | — | — | — | SFS38P30 | SFS38P32 | SFS38P45 | SFS38P47 |
| 1/2" BSPP | — | — | SFS12P10 | SFS12P15 | — | — | SFS12P30 | SFS12P32 | SFS12P45 | SFS12P47 |
| 3/4" BSPP | — | — | — | — | — | — | SFS34P30 | — | — | — |

| Thread Size | To suit probes with the following diameters | | | | | | | | | |
|-------------|---|----------|-----------------|------------------|----------|-----------------|-----------|------------------|------------------|--------------------|
| | 7/32" 5.5mm | 6.0mm | (1/4") 6.4mm | (5/16") 7.9mm | 8.0mm | (3/8") 9.5mm | 12.0mm | (1/2") 12.7mm | (5/8") 15.9mm | (13/16") 21.3mm |
| 1/8" BSPP | SFS18P55 | SFS18P60 | SFS18P64 | — | — | — | — | — | — | — |
| 1/4" BSPP | SFS14P55 | SFS14P60 | SFS14P64 | SFS14P79 | SFS14P80 | — | — | — | — | — |
| 3/8" BSPP | SFS38P55 | SFS38P60 | SFS38P64 | SFS38P79 | SFS38P80 | SFS38P95 | — | SFS38P127 | — | — |
| 1/2" BSPP | SFS12P55 | SFS12P60 | SFS12P64 | SFS12P79 | SFS12P80 | SFS12P95 | SFS12P120 | SFS12P127 | SFS12P159 | — |
| 3/4" BSPP | — | SFS34P60 | SFS34P64 | SFS34P79 | SFS34P80 | SFS34P95 | SFS34P120 | SFS34P127 | SFS34P159 | SFS34P213 |
| 1" BSPP | — | SFS1P60 | SFS1P64 | SFS1P79 | SFS1P80 | — | SFS1P120 | SFS1P127 | SFS1P159 | SFS1P213 |

Other thread sizes are available, please contact us for details.

Compression Fittings

SFS Single Ferrule 316 Stainless Steel Fittings - NPT Threads




Spare / replacement olives are available. Please see page 8 for details.

| Thread Size | To suit probes with the following diameters | | | | | | | | | |
|-------------|---|--------|-----------|-----------|------------------|-----------|-----------|-----------------|----------|-------------------|
| | 0.5mm | 0.75mm | 1.0mm | 1.5mm | (1/16") 1.6mm | 2.0mm | 3.0mm | (1/8") 3.2mm | 4.5mm | (3/16") 4.76mm |
| 1/16" NPT | SFS116N05 | — | SFS116N10 | SFS116N15 | SFS116N16 | SFS116N20 | SFS116N30 | — | — | — |
| 1/8" NPT | SFS18N05 | — | SFS18N10 | SFS18N15 | SFS18N16 | SFS18N20 | SFS18N30 | SFS18N32 | SFS18N45 | SFS18N47 |
| 1/4" NPT | — | — | SFS14N10 | SFS14N15 | SFS14N16 | SFS14N20 | SFS14N30 | SFS14N32 | SFS14N45 | SFS14N47 |
| 3/8" NPT | — | — | — | — | — | — | SFS38N30 | SFS38N32 | SFS38N45 | SFS38N47 |
| 1/2" NPT | — | — | SFS12N10 | SFS12N15 | — | — | SFS12N30 | SFS12N32 | SFS12N45 | SFS12N47 |
| 3/4" NPT | — | — | — | — | — | — | SFS34N30 | — | — | — |

| Thread Size | To suit probes with the following diameters | | | | | | | | | |
|-------------|---|----------|-----------------|------------------|----------|-----------------|-----------|------------------|------------------|--------------------|
| | (7/32") 5.5mm | 6.0mm | (1/4") 6.4mm | (5/16") 7.9mm | 8.0mm | (3/8") 9.5mm | 12.0mm | (1/2") 12.7mm | (5/8") 15.9mm | (13/16") 21.3mm |
| 1/8" NPT | SFS18N55 | SFS18N60 | SFS18N64 | — | — | — | — | — | — | — |
| 1/4" NPT | SFS14N55 | SFS14N60 | SFS14N64 | SFS14N79 | SFS14N80 | — | — | — | — | — |
| 3/8" NPT | SFS38N55 | SFS38N60 | SFS38N64 | SFS38N79 | SFS38N80 | SFS38N95 | — | SFS38N127 | — | — |
| 1/2" NPT | SFS12N55 | SFS12N60 | SFS12N64 | SFS12N79 | SFS12N80 | SFS12N95 | SFS12N120 | SFS12N127 | SFS12N159 | — |
| 3/4" NPT | — | SFS34N60 | SFS34N64 | SFS34N79 | SFS34N80 | SFS34N95 | SFS34N120 | SFS34N127 | SFS34N159 | SFS34N213 |
| 1" NPT | — | SFS1N60 | SFS1N64 | SFS1N79 | SFS1N80 | — | SFS1N120 | SFS1N127 | SFS1N159 | SFS1N213 |

Other thread sizes are available, please contact us for details.

DFS Double Ferrule 316 Stainless Steel Fittings - BSPT Threads



Spare / replacement olive sets are available. Please contact us for details.

Double Ferrule

The double ferrule system gives a tighter seal against the media. When tightened, the front ferrule creates a full-face seal on the tapered mouth of the fitting whilst the rear ferrule provides a mechanical grip on the sensor itself. In this design front and rear ferrules move axially instead of in a rotary motion so no torque is transferred to the sensor during installation.


| Thread Size | To suit probes with the following diameters | | | | | | |
|-------------|---|-----------------|----------|-------------------|----------|-----------------|------------------|
| | 3.0mm | (1/8") 3.2mm | 4.5mm | (3/16") 4.76mm | 6.0mm | (1/4") 6.4mm | (5/16") 7.9mm |
| 1/16" BSPT | DFS116T30 | — | — | — | — | — | — |
| 1/8" BSPT | DFS18T30 | DFS18T32 | DFS18T45 | DFS18T47 | DFS18T60 | DFS18T64 | — |
| 1/4" BSPT | DFS14T30 | DFS14T32 | DFS14T45 | DFS14T47 | DFS14T60 | DFS14T64 | DFS14T79 |
| 3/8" BSPT | DFS38T30 | DFS38T32 | DFS38T45 | DFS38T47 | DFS38T60 | DFS38T64 | DFS38T79 |
| 1/2" BSPT | DFS12T30 | DFS12T32 | DFS12T45 | DFS12T47 | DFS12T60 | DFS12T64 | DFS12T79 |
| 3/4" BSPT | — | — | — | — | DFS34T60 | DFS34T64 | DFS34T79 |
| 1" BSPT | — | — | — | — | DFS1T60 | DFS1T64 | DFS1T79 |

| Thread Size | To suit probes with the following diameters | | | | | | |
|-------------|---|-----------------|-----------|------------------|------------------|------------------|--------------------|
| | 8.0mm | (3/8") 9.5mm | 12.0mm | (1/2") 12.7mm | (5/8") 15.9mm | (3/4") 19.5mm | (13/16") 21.3mm |
| 1/8" BSPT | — | — | — | — | — | — | — |
| 1/4" BSPT | DFS14T80 | — | — | — | — | — | — |
| 3/8" BSPT | DFS38T80 | DFS38T95 | — | DFS38T127 | — | — | — |
| 1/2" BSPT | DFS12T80 | DFS12T95 | DFS12T120 | DFS12T127 | DFS12T159 | — | — |
| 3/4" BSPT | DFS34T80 | DFS34T95 | DFS34T120 | DFS34T127 | DFS34T159 | DFS34T195 | DFS34T213 |
| 1" BSPT | DFS1T80 | — | DFS1T120 | DFS1T127 | DFS1T159 | DFS1T195 | DFS1T213 |

Other thread sizes are available, please contact us for details.

Compression Fittings

DFS Double Ferrule 316 Stainless Steel Fittings - BSPP Threads




Spare / replacement olive sets are available. Please contact us for details.

| Thread Size | To suit probes with the following diameters | | | | | | |
|-------------|---|-----------------|----------|-------------------|----------|-----------------|------------------|
| | 3.0mm | (1/8") 3.2mm | 4.5mm | (3/16") 4.76mm | 6.0mm | (1/4") 6.4mm | (5/16") 7.9mm |
| 1/16" BSPP | DFS116P30 | — | — | — | — | — | — |
| 1/8" BSPP | DFS18P30 | DFS18P32 | DFS18P45 | DFS18P47 | DFS18P60 | DFS18P64 | — |
| 1/4" BSPP | DFS14P30 | DFS14P32 | DFS14P45 | DFS14P47 | DFS14P60 | DFS14P64 | DFS14P79 |
| 3/8" BSPP | DFS38P30 | DFS38P32 | DFS38P45 | DFS38P47 | DFS38P60 | DFS38P64 | DFS38P79 |
| 1/2" BSPP | DFS12P30 | DFS12P32 | DFS12P45 | DFS12P47 | DFS12P60 | DFS12P64 | DFS12P79 |
| 3/4" BSPP | — | — | — | — | DFS34P60 | DFS34P64 | DFS34P79 |
| 1" BSPP | — | — | — | — | DFS1P60 | DFS1P64 | DFS1P79 |

| Thread Size | To suit probes with the following diameters | | | | | | |
|-------------|---|-----------------|-----------|------------------|------------------|------------------|--------------------|
| | 8.0mm | (3/8") 9.5mm | 12.0mm | (1/2") 12.7mm | (5/8") 15.9mm | (3/4") 19.5mm | (13/16") 21.3mm |
| 1/8" BSPP | — | — | — | — | — | — | — |
| 1/4" BSPP | DFS14P80 | — | — | — | — | — | — |
| 3/8" BSPP | DFS38P80 | DFS38P95 | — | DFS38P127 | — | — | — |
| 1/2" BSPP | DFS12P80 | DFS12P95 | DFS12P120 | DFS12P127 | DFS12P159 | — | — |
| 3/4" BSPP | DFS34P80 | DFS34P95 | DFS34P120 | DFS34P127 | DFS34P159 | DFS34P195 | DFS34P213 |
| 1" BSPP | DFS1P80 | — | DFS1P120 | DFS1P127 | DFS1P159 | DFS1P195 | DFS1P213 |

Other thread sizes are available, please contact us for details.

DFS Double Ferrule 316 Stainless Steel Fittings - NPT Threads



Spare / replacement olive sets are available. Please contact us for details.


| Thread Size | To suit probes with the following diameters | | | | | | |
|-------------|---|-----------------|----------|-------------------|----------|-----------------|------------------|
| | 3.0mm | (1/8") 3.2mm | 4.5mm | (3/16") 4.76mm | 6.0mm | (1/4") 6.4mm | (5/16") 7.9mm |
| 1/16" NPT | DFS116N30 | — | — | — | — | — | — |
| 1/8" NPT | DFS18N30 | DFS18N32 | DFS18N45 | DFS18N47 | DFS18N60 | DFS18N64 | — |
| 1/4" NPT | DFS14N30 | DFS14N32 | DFS14N45 | DFS14N47 | DFS14N60 | DFS14N64 | DFS14N79 |
| 3/8" NPT | DFS38N30 | DFS38N32 | DFS38N45 | DFS38N47 | DFS38N60 | DFS38N64 | DFS38N79 |
| 1/2" NPT | DFS12N30 | DFS12N32 | DFS12N45 | DFS12N47 | DFS12N60 | DFS12N64 | DFS12N79 |
| 3/4" NPT | — | — | — | — | DFS34N60 | DFS34N64 | DFS34N79 |
| 1" NPT | — | — | — | — | DFS1N60 | DFS1N64 | DFS1N79 |

| Thread Size | To suit probes with the following diameters | | | | | | |
|-------------|---|-----------------|-----------|------------------|------------------|------------------|--------------------|
| | 8.0mm | (3/8") 9.5mm | 12.0mm | (1/2") 12.7mm | (5/8") 15.9mm | (3/4") 19.5mm | (13/16") 21.3mm |
| 1/8" NPT | — | — | — | — | — | — | — |
| 1/4" NPT | DFS14N80 | — | — | — | — | — | — |
| 3/8" NPT | DFS38N80 | DFS38N95 | — | DFS38N127 | — | — | — |
| 1/2" NPT | DFS12N80 | DFS12N95 | DFS12N120 | DFS12N127 | DFS12N159 | — | — |
| 3/4" NPT | DFS34N80 | DFS34N95 | DFS34N120 | DFS34N127 | DFS34N159 | DFS34N195 | DFS34N213 |
| 1" NPT | DFS1N80 | — | DFS1N120 | DFS1N127 | DFS1N159 | DFS1N195 | — |

Other thread sizes are available, please contact us for details.

Compression Fittings

DFSM Double Ferrule 316 Stainless Steel Fittings - Metric Threads




Spare / replacement olive sets are available. Please contact us for details.

| Thread Size | To suit probes with the following diameters | | | | | |
|-------------|---|-----------|-----------|-----------|-----------|-----------|
| | 3.0mm | 3.2mm | 4.5mm | 6.0mm | 6.4mm | 8.0mm |
| M6 | — | — | — | — | — | — |
| M8 | DFSM8-30 | DFSM8-32 | DFSM8-45 | — | — | — |
| M10 | DFSM10-30 | — | DFSM10-45 | DFSM10-60 | — | — |
| M12 | DFSM12-30 | — | DFSM12-45 | DFSM12-60 | — | DFSM12-80 |
| M14 | DFSM14-30 | — | — | DFSM14-60 | — | DFSM14-80 |
| M16 | DFSM16-30 | — | — | DFSM16-60 | — | — |
| M20 | DFSM20-30 | DFSM20-32 | DFSM20-45 | DFSM20-60 | — | — |
| M24 | DFSM24-30 | DFSM24-32 | DFSM24-45 | DFSM24-60 | DFSM24-64 | — |

Other thread sizes are available, please contact us for details.


SFSB Single Ferrule 316 Stainless Steel Fittings - Blank Threads



Spare / replacement olives are available. Please see page 8 for details.

| Thread Size | To suit probes with the following diameters | | | |
|-------------|---|--------|--------|--------|
| | 1.0mm | 1.5mm | 2.0mm | 3.0mm |
| Blank | SFSB10 | SFSB15 | SFSB20 | SFSB30 |

SFSM Single Ferrule, Counter Bored 316 Stainless Steel Fittings - Metric Threads




Spare / replacement olives are available. Please see page 8 for details.

| Thread Size | To suit probes with the following diameters | | | | | | | | |
|-------------|---|-------------|-------------|-------------|-------------|-------------------|------------------|-------------|-------------|
| | 1.0mm | 1.5mm | 2.0mm | 3.0mm | 4.5mm | (3/16") 4.76mm | (7/32") 5.5mm | 6.0mm | 8.0mm |
| M16 | SFSM16-10CB | SFSM16-15CB | SFSM16-20CB | SFSM16-30CB | SFSM16-45CB | — | SFSM16-55CB | SFSM16-60CB | SFSM16-80CB |
| M18 | — | — | — | — | — | — | — | SFSM18-60CB | — |
| M20 | SFSM20-10CB | SFSM20-15CB | SFSM20-20CB | SFSM20-30CB | SFSM20-45CB | SFSM20-47CB | SFSM20-55CB | SFSM20-60CB | SFSM20-80CB |
| M24 | — | SFSM24-15CB | — | SFSM24-30CB | — | — | — | SFSM24-60CB | — |

Other thread sizes are available, please contact us for details.

Compression Fittings

SFB Single Ferrule Brass Fittings - BSPT Threads




Spare / replacement olives are available.
Please see page 8 for details.

| Thread Size | To suit probes with the following diameters | | | | | | | | | | | |
|-------------|---|----------|------------------|----------|----------|-----------------|----------|-------------------|----------|-----------------|----------|------------------|
| | 1.0mm | 1.5mm | (1/16") 1.6mm | 2.0mm | 3.0mm | (1/8") 3.2mm | 4.5mm | (3/16") 4.76mm | 6.0mm | (1/4") 6.4mm | 8.0mm | (1/2") 12.7mm |
| 1/8" BSPT | SFB18T10 | SFB18T15 | SFB18T16 | SFB18T20 | SFB18T30 | SFB18T32 | SFB18T45 | SFB18T47 | SFB18T60 | SFB18T64 | — | — |
| 1/4" BSPT | — | SFB14T15 | SFB14T16 | SFB14T20 | SFB14T30 | SFB14T32 | SFB14T45 | SFB14T47 | SFB14T60 | SFB14T64 | — | — |
| 3/8" BSPT | — | — | — | — | SFB38T30 | — | SFB38T45 | — | SFB38T60 | SFB38T64 | — | — |
| 1/2" BSPT | — | — | — | — | SFB12T30 | SFB12T32 | SFB12T45 | SFB12T47 | SFB12T60 | SFB12T64 | SFB12T80 | SFB12T127 |
| 3/4" BSPT | — | — | — | — | SFB34T30 | — | — | — | SFB34T60 | — | — | SFB34T127 |

Other thread sizes are available, please contact us for details.

SFB Single Ferrule Brass Fittings - BSPP Threads




Spare / replacement olives are available.
Please see page 8 for details.

| Thread Size | To suit probes with the following diameters | | | | | | | | | | | |
|-------------|---|----------|------------------|----------|----------|-----------------|----------|-------------------|----------|-----------------|----------|------------------|
| | 1.0mm | 1.5mm | (1/16") 1.6mm | 2.0mm | 3.0mm | (1/8") 3.2mm | 4.5mm | (3/16") 4.76mm | 6.0mm | (1/4") 6.4mm | 8.0mm | (1/2") 12.7mm |
| 1/8" BSPP | SFB18P10 | SFB18P15 | SFB18P16 | SFB18P20 | SFB18P30 | SFB18P32 | SFB18P45 | SFB18P47 | SFB18P60 | SFB18P64 | — | — |
| 1/4" BSPP | — | SFB14P15 | SFB14P16 | SFB14P20 | SFB14P30 | SFB14P32 | SFB14P45 | SFB14P47 | SFB14P60 | SFB14P64 | — | — |
| 3/8" BSPP | — | — | — | — | SFB38P30 | — | SFB38P45 | — | SFB38P60 | SFB38P64 | — | — |
| 1/2" BSPP | — | — | — | — | SFB12P30 | SFB12P32 | SFB12P45 | SFB12P47 | SFB12P60 | SFB12P64 | SFB12P80 | SFB12P127 |
| 3/4" BSPP | — | — | — | — | SFB34P30 | — | — | — | SFB34P60 | — | — | SFB34P127 |

Other thread sizes are available, please contact us for details.

SFB Single Ferrule Brass Fittings - NPT Threads




Spare / replacement olives are available.
Please see page 8 for details.

| Thread Size | To suit probes with the following diameters | | | | | | | | | | | |
|-------------|---|----------|------------------|----------|----------|-----------------|----------|-------------------|----------|-----------------|----------|------------------|
| | 1.0mm | 1.5mm | (1/16") 1.6mm | 2.0mm | 3.0mm | (1/8") 3.2mm | 4.5mm | (3/16") 4.76mm | 6.0mm | (1/4") 6.4mm | 8.0mm | (1/2") 12.7mm |
| 1/8" NPT | SFB18N10 | SFB18N15 | SFB18N16 | SFB18N20 | SFB18N30 | SFB18N32 | SFB18N45 | SFB18N47 | SFB18N60 | SFB18N64 | — | — |
| 1/4" NPT | — | SFB14N15 | SFB14N16 | SFB14N20 | SFB14N30 | SFB14N32 | SFB14N45 | SFB14N47 | SFB14N60 | SFB14N64 | — | — |
| 3/8" NPT | — | — | — | — | SFB38N30 | — | SFB38N45 | — | SFB38N60 | SFB38N64 | — | — |
| 1/2" NPT | — | — | — | — | SFB12N30 | SFB12N32 | SFB12N45 | SFB12N47 | SFB12N60 | SFB12N64 | SFB12N80 | SFB12N127 |
| 3/4" NPT | — | — | — | — | SFB34N30 | — | — | — | SFB34N60 | — | — | SFB34N127 |

Other thread sizes are available, please contact us for details.

Compression Fittings

SFBM Single Ferrule, Counter Bored Brass Fittings - Metric Threads






Spare / replacement olives are available. Please see below for details.

| Thread Size | To suit probes with the following diameters | | | | | | | | |
|-------------|---|-------------|-------------|-------------|-------------|-------------------|------------------|-------------|-------------|
| | 1.0mm | 1.5mm | 2.0mm | 3.0mm | 4.5mm | (3/16") 4.76mm | (7/32") 5.5mm | 6.0mm | 8.0mm |
| M16 | SFBM16-10CB | SFBM16-15CB | SFBM16-20CB | SFBM16-30CB | SFBM16-45CB | — | SFBM16-55CB | SFBM16-60CB | SFBM16-80CB |
| M20 | SFBM20-10CB | SFBM20-15CB | SFBM20-20CB | SFBM20-30CB | SFBM20-45CB | — | SFBM20-55CB | SFBM20-60CB | SFBM20-80CB |
| M24 | — | — | — | SFBM24-30CB | — | — | — | SFBM24-60CB | — |

Other thread sizes are available, please contact us for details.

SFNB Single Ferrule Nickel Plated Brass Fittings - BSPT, BSPP and NPT Threads



| Thread Size | To suit probes with the following diameters | | | |
|-------------|---|-----------|-----------|-----------|
| | 1.5mm | 3.0mm | 4.5mm | 6.0mm |
| 1/8" BSPT | SFNB18T15 | SFNB18T30 | SFNB18T45 | SFNB18T60 |
| 1/4" BSPT | SFNB14T15 | SFNB14T30 | SFNB14T45 | SFNB14T60 |
| 1/2" BSPT | — | SFNB12T30 | — | SFNB12T60 |
| 1/8" BSPP | SFNB18P15 | SFNB18P30 | SFNB18P45 | SFNB18P60 |
| 1/4" BSPP | SFNB14P15 | SFNB14P30 | SFNB14P45 | SFNB14P60 |
| 1/2" BSPP | — | SFNB12P30 | — | SFNB12P60 |
| 1/2" NPT | — | SFNB12N30 | — | SFNB12N60 |

Other thread sizes are available, please contact us for details. Olives are Nickel Plated Brass, however the plating can wear under compression.

0 Replacement Single Ferrule Olives in Stainless Steel, Brass and PTFE



Single Ferrule (SF)

| Style and Material | To suit probes with the following diameters | | | | | | | |
|--------------------|---|--------------|--------------|--------------|--------------|--------------|-----------------|--------------|
| | 0.5mm | 0.75mm | 1.0mm | 1.5mm | 2.0mm | 3.0mm | (1/8") 3.2mm | 4.5mm |
| SF Style St./St. | O-316-40-05 | O-316-45-075 | O-316-45-10 | O-316-45-15 | O-316-45-20 | O-316-45-30 | O-316-45-32 | O-316-60-45 |
| SF Style Brass | — | — | O-BRA-45-10 | O-BRA-45-15 | O-BRA-45-20 | O-BRA-45-30 | O-BRA-45-32 | — |
| SF Style PTFE | — | — | O-PTFE-60-10 | O-PTFE-60-15 | O-PTFE-60-20 | O-PTFE-60-30 | — | O-PTFE-60-45 |

| Style and Material | To suit probes with the following diameters | | | | | | | |
|--------------------|---|--------------|-----------------|--------------|-------------|--------------|------------------|------------------|
| | 4.76mm | 6.0mm | (1/4") 6.4mm | 8.0mm | 9.5mm | 12mm | (1/2") 12.7mm | (5/8") 15.9mm |
| SF Style St./St. | O-316-60-47 | O-316-60-60 | O-316-60-64 | O-316-60-80 | O-316-60-95 | O-316-60-120 | O-316-60-127 | O-316-60-159 |
| SF Style Brass | — | O-BRA-60-60 | — | O-BRA-60-80 | — | — | — | — |
| SF Style PTFE | — | O-PTFE-60-60 | — | O-PTFE-60-80 | — | — | — | — |

Other sizes are available, please contact us for details.



**PO Box 130
Uxbridge
UB8 2YS
United Kingdom
Tel: 01895 252222
International: +44 1895 252222
Email: info@tc.co.uk
Web: www.tc.co.uk**

© TC Ltd.
Issue Number: 0321

TC Ltd for Temperature Sensing, Measurement and Control